

There are four critical factors to getting the most enjoyment and reliability out of your Ellsworth frame:

- 1) Proper set-up of suspension components. (Note #1)
- 2) Proper fork for your frame. (Note #2)
- 3) Seat post insertion minimum of 10cm / 4" at all times. (Note #3)
- 4) Avoid direct impacts with hard surfaces (Note #4)

Note #1: This warranty does not cover improper set up of the suspension unit (rear shock unit) which if improperly set up can cause damage or failure to a frame. Individual riding style, terrain, and technique can require specific shock unit tuning. Shocks require regular maintenance and or replacement by a qualified mechanic to perform properly. Shocks that have not been replaced or maintained or replaced can cause severe damage to your frame and void any frame warranty. Please have your shocks serviced regularly. Read the owners manual, which shipped with your bike, or you may download a copy from the www.ellsworthbikes.com FAQ section, which offers further information concerning shock set up.

Note # 2: This warranty does not cover frame damage or failure due to the selection and application of a fork with travel or length variations outside the intended or recommended fork use, travel, and length as disclosed in the owner's manual that shipped with your frame, or available on line at www.ellsworthbikes.com. Use of components, or tires that do not match the intended use of the frame, will void the warranty, i.e. DH tires or fork on an XC bike. Select the frame for your riding style, and use the bike as designed. Your frame shipped with a warning sticker that advises as to fork type and length, and frame use.

Note # 3: This warranty does not cover damage to a frame due to inadequate insertion of the seat post, or insertion and use of a seat post not properly sized for the frame. If the seat post installed in your frame does not have a minimum insertion of 10 cm, and doesn't slip snugly in the frame, it may be too short, or too small of diameter. You should contact your authorized dealer to properly size the seat post for your frame. All Ellsworth frames use either a 27.2mm or 27.4mm post to attain proper fit. It is the owners express responsibility to properly fit the post to the bike, regardless of the frames set tube actual Internal Diameter.

Note #4: Dents, dings, scratches and other cosmetic damage to the lightweight alloy tubes can be avoided by not subjecting your frame to *any* direct impacts with a hard surface.

IMPORTANT:

Recycling is inherently dangerous. Proper equipment set up is crucial in helping to prevent equipment failure and resulting serious injury or death. Please read and understand the following warnings.

Forks, unladen, must be properly matched to frame in topout-to-crown length, regardless of travel (check with dealer, manufacturer).

Model	Recommended Fork Travel
Trail	80-115mm
Des	80-100mm
Enlightenment	80-100mm
Isis	80-130mm
Distance	100-150mm
Joker	125-200mm
Moment	125-150mm
Dare	125-200mm
Specialist	80-130mm
Epiphany	100-130mm
Rogue	130-200mm
Witness	100-150mm
Chaos	125-200mm

Minimum seat post insertion is 10cm, regardless of markings on seatpost.

Use of this bike does not bestow any of the following: superhuman powers, ability to safely perform insane stunts, and gravity defies, or resistance to force of nature (wind).

Wear proper protective gear and obey all traffic laws, street and trail etiquette. As with all machinery, misuse of the bike may result in serious (and embarrassing) injury or death!

Ellsworth Handcrafted Bicycles, Inc. is an environmentally sensitive company and has printed this card on 100% recycled paper.

MAIL THIS PORTION ALONG WITH A COPY OF YOUR SALES RECEIPT TO:

Ellsworth Handcrafted Bicycles, Inc.
16225 Highland Trails Dr., "B"
Ramona, CA 92065

FOLD HERE